



Standard		Basic load rating		Weight	Dimensions (mm)												
Designation	Linear Bearing	Dynamic	Static		Shaft	h	D	W	H	G	A	J	E	S1 x l	S2	C	L
		C N	Co N														
SC8UU	LM8UU	274	392	56	8	11	17	34	22	18	6	24	5	M4x8	3.4	18	30
SC10UU	LM10UU	372	549	90	10	13	20	40	26	21	8	28	6	M5x12	4.3	21	35
SC12UU	LM12UU	510	784	112	12	15	21	42	28	24	8	30.5	5.75	M5x12	4.3	26	36
SC13UU	LM13UU	510	784	123	13	15	22	44	30	24.5	8	33	5.5	M5x12	4.3	26	39
SC16UU	LM16UU	774	1180	189	16	19	25	50	38.5	32.5	9	36	7	M5x12	4.3	34	44
SC20UU	LM20UU	882	1370	237	20	21	27	54	41	35	11	40	7	M6x12	5.2	40	50
SC25UU	LM25UU	980	1570	555	25	26	38	76	51.5	42	12	54	11	M8x18	7	50	67
SC30UU	LM30UU	1570	2740	685	30	30	39	78	59.5	49	15	58	10	M8x18	7	58	72
SC35UU	LM35UU	1670	3140	1100	35	34	45	90	68	54	18	70	10	M8x18	7	60	80
SC40UU	LM40UU	2160	4020	1600	40	40	51	102	78	62	20	80	11	M10x25	8.7	60	90
SC50UU	LM50UU	3820	7940	3350	50	52	61	122	102	80	25	100	11	M10x25	8.7	80	110